

### TECHNICAL DATA SHEET CONTACT ADHESIVE

# **1. IDENTIFICATION OF THE SUBSTANCE AND COMPANY DETAILS**

#### **GLUECHEM**

Unit 2, Khanda Industrial Park, 16 Jockey Street, Stormill Tel:082 823 0523 Email: info@gluechem.co.za

#### TRADE NAME: CA 2000 CONTACT ADHESIVE

Chemical abstract no.: Mixture Chemical family: Solvent mixture NIOSH no.: Unknown Chemical name: Mixture Hazchem code: Unknown Synonyms: None UN no.: 2929 Toxic liquid, organics, NOS

CA 2000 contact adhesive is designed to form strong bonds between surfaces like wood, plastic, rubber, foam, cork, wood laminates, floor coverings etc. NOT SUITABLE FOR POLYSTYRENE.

### 2. PHYSICAL FORM

CA 2000 is a yellowish liquid.

#### 3. APPLICATION

Stir well before use. Ensure that surfaces to be bonded are clean, dry and free from any other barrier to adhesion. Apply a uniform coat of adhesion to both surfaces and allow to dry for 10 - 15 minutes. Contact bond and apply pressure to create a permanent bond. Keep container sealed in a cool dry place when not in use.

### 4. PROPERTIES

- High bond strengths,
- High heat resistance,
- Water resistance,
- Fast drying times,
- Long tack time.

## 5. STORAGE STABILITY

6 Months when stored in the original sealed containers within a temperature range of 10'C - 25'C



# 6. PRODUCT SAFETY

Highly flammable and should not be used in confined areas without adequate ventilation. The solvent blend used in this adhesive is highly flammable and should not be exposed to or used near a naked flame. Avoid prolonged breathing in of the vapour and contact with the skin. Refer to relevant safety data sheets for CBA 109 and Enprene thinners.

# 7. NON-WARRANTY

All products are manufactured to strict specifications. However, since we have no control over the conditions under which the purchaser stores, handles or uses these goods, we make no warranty, either expressed or implied with respect to these goods, their application properties or fitness for any purpose or the results to be obtained from their use.